




LOC		DIST		REVISIONS			
DF	DO	REV	PER	ECO	DATE	BY	APPV
Y		REV PER ECO	07-019177		08OCT07	PY	BW



1. THIS RECEPTACLE WILL MATE WITH ANY PLUG CONNECTOR WITH SAME INSERT ARRANGEMENT AS DEFINED BY MS18276-2.
2. MAXIMUM WIRE INSULATION USED WITH THIS RCPT. IS .054 DIA.
3. Be-Cu RETENTION CLIPS ARE INCLUDED IN INSERTS.
4. INSPECTION REQUIREMENTS PER R4383.
5. CONNECTOR SUPPLIED WITH 69 CONTACTS, AMP PART NUMBER 206071-1. INSPECTION REQUIREMENTS PER R4383 WITHOUT TESTS FOR HIGH ALTITUDE DIELECTRIC WITHSTANDING VOLTAGE AS CALLED FOR IN TABLE II SCREENING AND TESTING.
6. UL/CSA DESIGNATION STAMPED IN THIS AREA,OPTIONAL
7. SPECIAL TESTING PER GE DOCUMENT 20025720. CONNECTOR SUPPLIED WITH 72 CONTACTS, AMP P/N 206071-1.
8. RESTRICTED TO CAE ELECTRONICS ONLY.
9. THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311-P-4.



AMP P/N 206071-1
 GSFC P/N G-08-S1
 (SUPPLIED WITH 206064-6 AND 206064-8 ONLY)



REMARKS	DIA A	CUSTOMER P/N ON CONNECTOR	AMP P/N ON CONNECTOR	PART NUMBER	
SUPERSEDED BY 1996014-4	---	.120	8333648P1	1-206503-2	1-206503-2
	---	.120	570566-4	1-206503-1	1-206503-1
	8 9	.120	311P407-4S-B-12	206503-4	206503-9
	7	.120	20025720P1062S	206503-8	206503-8
	---	.154	SC81D139-044	206503-7	206503-7
	5	.120	R4383P62S	206503-6	206503-6
	4	.120	R4383P62S-2	206503-5	206503-5
	3	.120	311P407-4S-B-12	206503-4	206503-4
	---	.154	N/A	206503-3	206503-3
	---	.120	R9259P62S	206503-2	206503-2
	2	.154	311P407-4S-B-15	206503-1	206503-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0. PLC ± .005	1. PLC ± .005	2. PLC ± .005	3. PLC ± .005	4. PLC ± .005	ANGLES ± .1°
--------------------	--	---------------	---------------	---------------	---------------	---------------	--------------

MATERIAL: SEE CALLOUTS
 FINISH: SEE CALLOUTS

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN: A.J. GRAFF 12-21-92
 CHK: D. MILLER 12-21-92
 APPV: D. MILLER 12-21-92
 NAME: AMP
 PRODUCT SPEC: AMPLIMITE RCPT ASSY, NON-MAGNETIC, SHELL SIZE 4,62 POSITION
 APPLICATION SPEC: ---
 WEIGHT: ---
 SIZE: A1
 CAGE CODE: 00779
 DRAWING NO: 206503
 RESTRICTED TO: ---
 CUSTOMER DRAWING: ---
 SCALE: 4:1
 SHEET: 1 of 1
 REV: Y